


NPDES PERMIT NO. GA0001465

Flow Mit 2008.ppt



PLANT MITCHELL ASH POND COTREATMENT SUMMARY TABLE

A) DRY WEAHTER PROCESS FLOWS Ash Transport Water 100% Recycle 01C Low Volume Waste (LVW) 01D Coal Pile Runoff (Incl. in LVW) Total Dry Weather (Process) Flow			(Maxii	mum Flows U 0.00 MGD 10.37 MGD 0.00 MGD 10.37 MG	950	0 GPM 7200 GPM 0 GPM	
B) RAINFALL RUNOFF (Using SCS Method) Ash Pond Surface Area - Wet Dry Pond Area				27.25 15.75			
Total Runoff Area				43.0 Acres			
10-year, 24 hour storm Annual Rainfall Equivalent Direct Run-off			6.50 inches 49.76 5.4 inches		(0.136 inches/da	ay)	
TOTAL Rainfall Runoff				6.31 MG			
C) REQUIRED WATER VOLUME							
(A) Dry Weather Flow + Rainfall Runoff =				16.68 MG	OR	82,571 CY	
D) ASH POND RE From Ash Mana Projected Rema YEAR CU YDS MG	agement Proje	ORAGE (See No ctions 2008 – 201 olume for Wet Sto 2009 82,571 16.68	3 (NO Projec orage on 12/31 2010 82,571	2011 82,571		2012 82,571	2013 82,571
			16.68	16.68		16.68	16.68
E) AVAILABLE VO	OLUME on 12	2/31/2013					

FROM ABOVE, (E) IS EQUAL TO (C), THEREFORE ASH POND CAPACITY IS SUFFICIENT

NOTES:

See (D) Above and Note 3 Below

 The rainfall runoff was determined using Soil Conservation Services (SCS) Method and Georgia manual for Sediment and Erosion Control, 2000 edition.

16.68 MG

82,571 CY

- 2. Strict Interpretation uses elevation 187.5, which represents current operating level.
- Volume projected for Strict Interpretation through 2013 assumes ash disposal rates remain as projected and that dry storage activities will maintain storage volume above minimum required for co-treatment purposes.